

WHAT IS CLAIMED IS:

1. A display device comprising:

a gamma correction circuit;

an image signal processing circuit connected with an output line of said gamma

correction circuit; and

a plurality of photosensors for changing an output voltage of the gamma correction circuit in accordance with a brightness of a surrounding.

2. A display device according to claim 1, wherein said display device is a liquid crystal display device or an electroluminescence display device.

3. A display device according to claim 1, wherein each of said photosensors has a photoelectric conversion layer comprising amorphous silicon.

4. A display device according to claim 1, wherein said display device is incorporated into an electronic equipment selected from the group consisting of a video camera, a digital camera, a projector, a head-mounted display, a car navigation system, a car stereo, a personal computer, and a portable information terminal.

5. A display device comprising:

a first substrate;

a second substrate fixed to said first substrate;

a gamma correction circuit;

an image signal processing circuit connected with an output line of said gamma correction circuit; and

a plurality of photosensors, formed on said second substrate, for changing an output voltage of said gamma correction circuit in accordance with a brightness of a surrounding.

6. A display device according to claim 5, wherein said display device is a liquid crystal display device or an electroluminescence display device.

7. A display device according to claim 5, wherein each of said photosensors has a photoelectric conversion layer comprising amorphous silicon.

8. A display device according to claim 5, wherein said display device is incorporated into an electronic equipment selected from the group consisting of a video camera, a digital camera, a projector, a head-mounted display, a car navigation system, a car stereo, a personal computer, and a portable information terminal.

9. A display device comprising:  
a plurality of photosensors for detecting a brightness of a surrounding; and  
a gamma correction circuit for outputting a voltage for determining a period that a pixel is in a light state in accordance with electrical signals from said plurality of photosensors.

10. A display device according to claim 9, wherein said display device is a liquid crystal display device or an electroluminescence display device.

11. A display device according to claim 9, wherein each of said photosensors has a photoelectric conversion layer comprising amorphous silicon.

12. A display device according to claim 9, wherein said display device is incorporated  
into an electronic equipment selected from the group consisting of a video camera, a digital  
camera, a projector, a head-mounted display, a car navigation system, a car stereo, a personal  
5 computer, and a portable information terminal.

13. A display device comprising:  
a plurality of photosensors provided on an peripheral portion of a substrate;  
a source follower circuit connected with said plurality of photosensors;  
a gamma correction circuit connected with said source follower circuit;  
an image signal amplifying circuit connected with said gamma correction circuit;  
a source signal line driver circuit connected with said image signal amplifying circuit;  
10 and  
a pixel portion which is connected with said source signal line driver circuit and  
15 formed on said substrate.

14. A display device according to claim 13, wherein said pixel portion has at least a  
pixel electrode, a liquid crystal layer, and a counter electrode.

20 15. A display device according to claim 13, wherein said pixel portion has at least a  
pixel electrode and a light emitting layer.

16. A display device according to claim 13, wherein each of said photosensors has a  
photoelectric conversion layer comprising amorphous silicon.

25

17. A display device according to claim 13, wherein said display device is incorporated into an electronic equipment selected from the group consisting of a video camera, a digital camera, a projector, a head-mounted display, a car navigation system, a car stereo, a personal computer, and a portable information terminal.

5

18. A display device comprising:

a first substrate;

a second substrate;

a plurality of photosensors which are formed on said second substrate and fixed to an outer portion of said first substrate;

a source follower circuit connected with said plurality of photosensors;

a gamma correction circuit connected with said source follower circuit;

an image signal amplifying circuit connected with said gamma correction circuit;

a source signal line driver circuit connected with said image signal amplifying circuit;

and

a pixel portion which is connected with said source signal line driver circuit and formed on said first substrate.

19. A display device according to claim 18, wherein said pixel portion has at least a pixel electrode, a liquid crystal layer, and a counter electrode.

20. A display device according to claim 18, wherein said pixel portion has at least a pixel electrode and a light emitting layer.

21. A display device according to claim 18, wherein each of said photosensors has a

photoelectric conversion layer comprising amorphous silicon.

22. A display device according to claim 18, wherein said display device is incorporated into an electronic equipment selected from the group consisting of a video camera, a digital camera, a projector, a head-mounted display, a car navigation system, a car stereo, a personal computer, and a portable information terminal.

23. A display device comprising:

a gamma correction circuit:

an image signal processing circuit connected with an output line of said gamma correction circuit; and

a plurality of photosensors for changing an output voltage of the gamma correction circuit in accordance with a brightness of a surrounding,

wherein each of said photosensors has a photoelectric conversion layer comprising amorphous silicon.

24. A display device according to claim 23, wherein said display device is a liquid crystal display device or an electroluminescence display device.

25. A display device according to claim 23, wherein said display device is incorporated into an electronic equipment selected from the group consisting of a video camera, a digital camera, a projector, a head-mounted display, a car navigation system, a car stereo, a personal computer, and a portable information terminal.

26. A method of manufacturing a display device, comprising the steps of:

forming a pixel portion using a thin film transistor on a first substrate;  
forming a photosensor on a second substrate; and  
fixing the second substrate to said first substrate.

5 27. A method of manufacturing a display device according to claim 26, wherein in the pixel portion at least, a pixel electrode, a liquid crystal layer, and a counter electrode are formed.

10 28. A method of manufacturing a display device according to claim 26, wherein in the pixel portion, at least a pixel electrode and a light emitting layer are formed.

29. A method of manufacturing a display device according to claim 26, wherein each of said photosensors has a photoelectric conversion layer comprising amorphous silicon.

15 30. A method of manufacturing a display device according to claim 26, wherein said display device is incorporated into an electronic equipment selected from the group consisting of a video camera, a digital camera, a projector, a head-mounted display, a car navigation system, a car stereo, a personal computer, and a portable information terminal.

20 31. A method of manufacturing a display device, comprising the steps of:  
forming a pixel portion, a driver circuit for driving said pixel portion, and a control circuit for controlling a brightness of said pixel portion, using a thin film transistor, on a first substrate;

forming a photosensor on a second substrate; and

25 fixing said second substrate to said first substrate to electrically connect said control

circuit with said photosensor.

32. A method of manufacturing a display device according to claim 31, wherein in the pixel portion at least, a pixel electrode, a liquid crystal layer, and a counter electrode are  
5 formed.

33. A method of manufacturing a display device according to claim 31, wherein in the pixel portion, at least a pixel electrode and a light emitting layer are formed.

34. A method of manufacturing a display device according to claim 31, wherein each of said photosensors has a photoelectric conversion layer comprising amorphous silicon.

35. A method of manufacturing a display device according to claim 31, wherein said display device is incorporated into an electronic equipment selected from the group consisting of a video camera, a digital camera, a projector, a head-mounted display, a car navigation system, a car stereo, a personal computer, and a portable information terminal.